

# SAFETY DATA SHEET

Revision Date 10-Jun-2015 Version 2

# 1. IDENTIFICATION

**Product identifier** 

**Product Name** MF Red Acrylic (VLA-12084)

Other means of identification

**Product Code** 18270 UN/ID no. UN1950 SKU(s) None

Recommended use of the chemical and restrictions on use No information available. **Recommended Use** Uses advised against No information available

Details of the supplier of the safety data sheet

**Manufacturer Address** Van Sickle Paint Mfg. Co.

PO Box 82222 Lincoln, NE 68501 Phone: 402-476-6558 Fax: 402-476-6749

Emergency telephone number

**Emergency Telephone** Chemtrec 1-800-424-9300

# 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Specific target organ toxicity (single exposure)	Category 3
Flammable aerosols	Category 1

#### **Emergency Overview**

# Danger

#### Hazard statements

Causes serious eye irritation May cause an allergic skin reaction May cause genetic defects

May cause cancer

May cause drowsiness or dizziness

Extremely flammable aerosol



**Appearance** No information available

Physical state Aerosol

Odor No information available

### **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing should not be allowed out of the workplace

Wear protective gloves

Use only outdoors or in a well-ventilated area

#### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

#### **Precautionary Statements - Storage**

Store locked up

Store in a well-ventilated place. Keep container tightly closed

# **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

### Hazards not otherwise classified (HNOC)

#### Other Information

 May be harmful if swallowed Unknown acute toxicity

0.64% of the mixture consists of ingredient(s) of unknown toxicity

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%	Trade Secret
Acetone	67-64-1	10 - 30	*
Propane	74-98-6	10 - 30	*
Methyl Amyl Ketone	110-43-0	10 - 30	*
Butane	106-97-8	7 - 13	*
Butyl Acetate	123-86-4	1 - 5	*
Diacetone Alcohol	123-42-2	1 - 5	*
Methyl Ethyl Ketoxime	96-29-7	1 - 5	*
Stoddard Solvent	8052-41-3	0.1 - 1	*

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

#### **Description of first aid measures**

General advice Immediate medical attention is required. In case of accident or unwellness, seek medical

advice immediately (show directions for use or safety data sheet if possible). If symptoms

persist, call a physician.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Keep eye wide open while rinsing. Call a physician immediately. Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and

upper eyelids. Consult a physician. If symptoms persist, call a physician.

**Skin Contact** Wash off immediately with plenty of water. Wash off immediately with soap and plenty of

water. Immediate medical attention is not required. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists,

call a physician.

**Inhalation** Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth

resuscitation. Immediate medical attention is required. If not breathing, give artificial

respiration. Move to fresh air in case of accidental inhalation of vapors. If symptoms persist,

call a physician.

**Ingestion** Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a

physician or poison control center immediately. Clean mouth with water and drink

afterwards plenty of water. Call a physician.

Self-protection of the first aider Remove all sources of ignition. Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

**Symptoms** No information available.

Indication of any immediate medical attention and special treatment needed

**Note to physicians**May cause sensitization of susceptible persons. Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

#### Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

#### Specific hazards arising from the chemical

In the event of fire and/or explosion do not breathe fumes. May cause sensitization by inhalation and skin contact. Thermal decomposition can lead to release of irritating and toxic gases and vapors.

**Explosion data** 

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

#### Protective equipment and precautions for firefighters

In the event of fire and/or explosion do not breathe fumes.

### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

**Personal precautions** Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate

ventilation, especially in confined areas. Use personal protective equipment as required.

Keep people away from and upwind of spill/leak.

Environmental precautions

**Environmental precautions** 

Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. See Section 12 for additional ecological information.

### Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so. Cover powder spill with plastic sheet or

tarp to minimize spreading. Dike far ahead of liquid spill for later disposal.

Methods for cleaning up Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal

binder, sawdust). Pick up and transfer to properly labeled containers. Soak up with inert

absorbent material.

## 7. HANDLING AND STORAGE

#### Precautions for safe handling

Advice on safe handling Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks,

flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Use with local exhaust ventilation. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not puncture or incinerate cans. Do

not stick pin or any other sharp object into opening on top of can.

#### Conditions for safe storage, including any incompatibilities

Storage Conditions Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep

containers tightly closed in a cool, well-ventilated place.

**Incompatible materials** Strong acids. Strong oxidizing agents. Chlorinated compounds.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone 67-64-1	STEL: 500 ppm TWA: 250 ppm	TWA: 1000 ppm TWA: 2400 mg/m³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m³ (vacated) STEL: 2400 mg/m³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m³
Propane 74-98-6	: See Appendix F: Minimal Oxygen Content	TWA: 1000 ppm TWA: 1800 mg/m³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m³	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m³
Methyl Amyl Ketone 110-43-0	TWA: 50 ppm	TWA: 100 ppm TWA: 465 mg/m³ (vacated) TWA: 100 ppm (vacated) TWA: 465 mg/m³	IDLH: 800 ppm TWA: 100 ppm TWA: 465 mg/m³
Butane 106-97-8	STEL: 1000 ppm	(vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m <sup>3</sup>	TWA: 800 ppm TWA: 1900 mg/m <sup>3</sup>
Butyl Acetate 123-86-4	STEL: 200 ppm TWA: 150 ppm	TWA: 150 ppm TWA: 710 mg/m³ (vacated) TWA: 150 ppm (vacated) TWA: 710 mg/m³ (vacated) STEL: 200 ppm (vacated) STEL: 950 mg/m³	IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m³ STEL: 200 ppm STEL: 950 mg/m³

Diacetone Alcohol 123-42-2	TWA: 50 ppm TWA: 50 ppm TWA: 240 mg/m³ (vacated) TWA: 50 ppm (vacated) TWA: 240 mg/m³		IDLH: 1800 ppm TWA: 50 ppm TWA: 240 mg/m³
Stoddard Solvent 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m³ (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m³	IDLH: 20000 mg/m³ Ceiling: 1800 mg/m³ 15 min TWA: 350 mg/m³

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

**Appropriate engineering controls** 

Showers **Engineering Controls** 

> Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles. Face protection shield.

Skin and body protection No special technical protective measures are necessary.

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved Respiratory protection

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

When using do not eat, drink or smoke. Regular cleaning of equipment, work area and **General Hygiene Considerations** 

clothing is recommended.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Information on basic physical and chemical properties

Physical state Aerosol

No information available No information available **Appearance** Odor Color No information available Odor threshold No information available

**Property** Values Remarks • Method

No information available Melting point/freezing point No information available >= -42 °C / -44 °F Boiling point / boiling range -104 °C / -155 °F Flash point

**Evaporation rate** No information available Flammability (solid, gas) No information available Flammability Limit in Air

Upper flammability limit: No information available Lower flammability limit: No information available Vapor pressure No information available Vapor density No information available

**Specific Gravity** 0.76

Water solubility No information available Solubility in other solvents No information available **Partition coefficient** No information available **Autoignition temperature** No information available No information available **Decomposition temperature** 

No information available Kinematic viscosity **Dynamic viscosity** No information available No information available **Explosive properties** 

Oxidizing properties No information available

**Other Information** 

Softening pointNo information availableMolecular weightNo information availableVOC Content (%)No information available

**Density** 6.38 lbs/gal

Bulk density No information available

Percent solids by weight 27.4% Percent volatile by weight 48.8% Percent solids by volume 19.2% Actual VOC (lbs/gal) 3.1 Actual VOC (grams/liter) 373 EPA VOC (lbs/gal) 4 EPA VOC (grams/liter) 484.1 EPA VOC (lb/gal solids) 16.2

# 10. STABILITY AND REACTIVITY

#### Reactivity

No data available

#### **Chemical stability**

Stable under recommended storage conditions.

# **Possibility of Hazardous Reactions**

None under normal processing.

#### Conditions to avoid

Heat, flames and sparks.

#### Incompatible materials

Strong acids. Strong oxidizing agents. Chlorinated compounds.

### **Hazardous Decomposition Products**

None known based on information supplied.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

Product Information No data available

**Inhalation** No data available.

**Eye contact** No data available.

**Skin Contact** No data available.

**Ingestion** No data available.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50 = 50100 mg/m³ ( Rat ) 8 h	
Acetone 67-64-1	= 5800 mg/kg ( Rat )	-		
Propane - 74-98-6		-	= 658 mg/L (Rat) 4 h	
Methyl Amyl Ketone 110-43-0	= 1600 mg/kg ( Rat ) = 1670 mg/kg ( Rat )	= 12.6 mL/kg(Rabbit)= 12600 μL/kg(Rabbit)	> 2000 ppm (Rat) 4 h	
Butane - 106-97-8		-	= 658 g/m³ (Rat) 4 h	
Butyl Acetate 123-86-4	= 10768 mg/kg (Rat)	> 17600 mg/kg (Rabbit)	= 390 ppm (Rat) 4 h	

Diacetone Alcohol 123-42-2	= 4 g/kg(Rat)	= 13500 mg/kg(Rabbit)	-
Methyl Ethyl Ketoxime 96-29-7	= 930 mg/kg(Rat)	= 0.2 mg/kg (Rabbit)	= 20 mg/L (Rat)4 h

#### Information on toxicological effects

**Symptoms** No information available.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization
Germ cell mutagenicity
Carcinogenicity
Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
No information available.

Chronic toxicity Repeated contact may cause allergic reactions in very susceptible persons. Avoid repeated

exposure. May cause adverse liver effects.

Target Organ Effects Central nervous system, Eyes, liver, Peripheral Nervous System (PNS), Respiratory

system, Skin.

**Aspiration hazard** No information available.

#### Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document mg/kg mg/l

### 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

54.71% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants Fish		Crustacea
Acetone 67-64-1	-	4.74 - 6.33: 96 h Oncorhynchus mykiss mL/L LC50 6210 - 8120: 96 h Pimephales promelas mg/L LC50 static 8300: 96 h Lepomis macrochirus mg/L LC50	10294 - 17704: 48 h Daphnia magna mg/L EC50 Static 12600 - 12700: 48 h Daphnia magna mg/L EC50
Methyl Amyl Ketone 110-43-0	-	126 - 137: 96 h Pimephales promelas mg/L LC50 flow-through	-
Butyl Acetate 123-86-4	674.7: 72 h Desmodesmus subspicatus mg/L EC50	100: 96 h Lepomis macrochirus mg/L LC50 static 17 - 19: 96 h Pimephales promelas mg/L LC50 flow-through 62: 96 h Leuciscus idus mg/L LC50 static	72.8: 24 h Daphnia magna mg/L EC50
Diacetone Alcohol 123-42-2	-	420: 96 h Lepomis macrochirus mg/L LC50 static 420: 96 h Lepomis macrochirus mg/L LC50	8750: 24 h Daphnia magna mg/L EC50
Methyl Ethyl Ketoxime 96-29-7	83: 72 h Desmodesmus subspicatus mg/L EC50	777 - 914: 96 h Pimephales promelas mg/L LC50 flow-through 760: 96 h Poecilia reticulata mg/L LC50 static 320 - 1000: 96 h Leuciscus idus mg/L LC50 static	750: 48 h Daphnia magna mg/L EC50

#### Persistence and degradability

No information available.

#### **Bioaccumulation**

No information available.

Chemical Name	Partition coefficient
Acetone	-0.24
67-64-1	
Propane 74-98-6	2.3

Methyl Amyl Ketone 110-43-0	1.98
Butane 106-97-8	2.89
Butyl Acetate 123-86-4	1.81
Diacetone Alcohol 123-42-2	1.03
Methyl Ethyl Ketoxime 96-29-7	0.65

Other adverse effects No information available

# 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number U002 U220 U239

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone	-	Included in waste stream:	-	U002
67-64-1		F039		

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
Acetone 67-64-1	Ignitable
Butyl Acetate 123-86-4	Toxic

### 14. TRANSPORT INFORMATION

DOT

UN/ID no. UN1950
Proper shipping name Aerosols
Hazard Class 2.1

**Description** UN1950, Aerosols, 2.1

**Emergency Response Guide** 126

Number

**TDG** 

UN/ID no. UN1950
Proper shipping name Aerosols
Hazard Class 2.1

**Description** UN1950, Aerosols, 2.1

MEX

UN/ID no. UN1950 Proper shipping name Aerosols

Hazard Class 2

**Description** UN1950, Aerosols, 2

ICAO (air)

UN/ID no. UN1950
Proper shipping name Aerosols

\_\_\_\_\_

Hazard Class 2.1

Special Provisions A145, A167

**Description** UN1950, Aerosols, 2.1

IATA

**UN/ID no.** UN1950

Proper shipping name Aerosols, flammable

Hazard Class 2.1 ERG Code 10L

Special Provisions A145, A167, A802

**Description** UN1950, Aerosols, flammable, 2.1

**IMDG** 

UN/ID no. UN1950
Proper shipping name Aerosols
Hazard Class 2
EmS-No. F-D, S-U

**Special Provisions** 63,190, 277, 327, 344, 959

**Description** UN1950, Aerosols, 2

RID

UN/ID no. UN1950
Proper shipping name Aerosols
Hazard Class 2.1
Classification code 5F

**Description** UN1950, Aerosols, 2.1

<u>ADR</u>

UN/ID no. UN1950
Proper shipping name Aerosols
Hazard Class 2.1
Classification code 5F
Tunnel restriction code (D)

**Special Provisions** 190, 327, 344, 625

**Description** UN1950, Aerosols, 2.1, (D)

Labels 2.1

ADN

Proper shipping name Aerosols
Hazard Class 2.1
Classification code 5F

**Special Provisions** 190, 327, 344, 625 **Description** UN1950, Aerosols, 2.1

Hazard label(s) 2.1 Limited quantity (LQ) 1 L

Ventilation VE01, VE04

# 15. REGULATORY INFORMATION

**International Inventories** 

**TSCA** Complies **DSL/NDSL** Complies \* **EINECS/ELINCS** Complies \* **ENCS** Does not comply \* **IECSC** Complies \* Complies \* **KECL PICCS** Does not comply \* Does not comply \* **AICS** 

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

<sup>\*</sup> This product contains an unknown chemical, therefore, this product's compliance to the inventory list is NOT DETERMINED

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

### **US Federal Regulations**

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

# SARA 311/312 Hazard Categories

Acute health hazardYesChronic Health HazardYesFire hazardYesSudden release of pressure hazardNoReactive HazardNo

#### **CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Butyl Acetate	5000 lb	-	-	X
123-86-4				

### CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Acetone 67-64-1	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Butyl Acetate 123-86-4	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

### **US State Regulations**

#### **California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65	
Ethyl Benzene - 100-41-4	Carcinogen	
Toluene - 108-88-3	Developmental Female Reproductive	

### U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Acetone 67-64-1	X	X	X
Propane 74-98-6	X	X	X
Methyl Amyl Ketone 110-43-0	Х	Х	Х
Butane 106-97-8	X	X	X
Butyl Acetate 123-86-4	X	X	X
Diacetone Alcohol 123-42-2	Х	X	X
Propylene Glycol Methyl Ether 107-98-2	Х	X	X

Page 10 / 11

\_\_\_\_

Trimethyl Benzene (mixed isomers) 25551-13-7	Х	Х	Х
Toluene	X	X	X
108-88-3			

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

#### Hazardous air pollutants (HAPS) content

This product contains no reportable Hazardous Air Pollutants

# 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 4 Instability 0 Physical and Chemical

Properties \*

Health hazards 2 \* Flammability 4 Physical hazards 0 Personal protection X

Chronic Hazard Star Legend \*= Chronic Health Hazard

Revision Date

10-Jun-2015

**Revision Note** 

No information available

**Disclaimer** 

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Shipping information may vary based upon container size and shipping destination. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. The manufacturer assumes no responsibility for injury to the recipient or third persons, or for any damages to any property resulting from misuse of the product.

**End of Safety Data Sheet**