SAFETY DATA SHEET

1. Identification

Product identifier POWER CUT

METALWORKING FLUID

Other means of identification

SDS number Not applicable

METALWORKING FLUID Recommended use

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company name DOALL SAWING PRODUCTS

> A DOALL COMPANY 2375 Toughy Avenue Elk Grove Village, IL 60007

Telephone (General

Information)

Emergency telephone

number

Emergency telephone number (outside USA) 888-362-5572, Ext 65047

1-800-424-9300 (CHEMTREC)

1-703-527-3887 (CHEMTREC)

2. Hazard(s) identification

Physical hazards Not classified.

Category 2A **Health hazards** Serious eye irritation

Sensitization, skin Category 1

Environmental hazards Not classified. **OSHA** defined hazards Not classified.

Label elements



Signal word Warning

Causes serious eye irritation. May cause an allergic skin reaction. **Hazard statement**

Precautionary statement

Avoid breathing mist or vapor. Wash thoroughly after handling. Contaminated work clothing must Prevention

not be allowed out of the workplace. Wear eye protection/face protection. Wear protective gloves.

If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Response

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Wash

contaminated clothing before reuse.

Store away from incompatible materials. Storage

Dispose of contents/container in accordance with local/regional/national/international regulations. **Disposal**

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information Use in manufacturing processes only.

> The classified hazards shown on this SDS are associated with the product concentrate. These hazards are not expected under recommended use conditions and dilution.

Material name: POWER CUT SDS US 1/9

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES		64742-52-5	70 - 80
ALKANES C14-16, CHLORO		1372804-76-6	5 - 10
PETROLEUM SULFONIC ACID, SODIUM SALT		68608-26-4	3 - 5
4-(2-NITROBUTYL)MORPHOLINE		2224-44-4	<= 1
Other components below reportable	elevels		10 - 20

The exact percentages of hazardous ingredients have been withheld as a trade secret.

4. First-aid measures

Move to fresh air. Call a physician if symptoms develop or persist. Under normal conditions of Inhalation

intended use, this material is not expected to be an inhalation hazard.

Rinse skin with water. If skin irritation or rash occurs: Get medical advice/attention. Wash Skin contact

contaminated clothing before reuse.

Rinse with water. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical Eye contact

attention if irritation develops and persists.

Rinse mouth thoroughly. Do not give liquids. Do not induce vomiting. If vomiting occurs, keep head Ingestion

low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel

unwell.

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed

Direct contact with eyes may cause temporary irritation. Symptoms may include stinging, tearing,

redness, swelling, and blurred vision. May cause an allergic skin reaction.

Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

General information If exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in

attendance.

5. Fire-fighting measures

Foam. Dry chemical powder. Carbon dioxide (CO2). Use extinguishing measures that are Suitable extinguishing media

appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment

and precautions for firefighters

Wear suitable protective equipment.

Fire fighting equipment/instructions

Specific methods

General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: POWER CUT SDS US

Methods and materials for containment and cleaning up

Local authorities should be advised if significant spillages cannot be contained. This product is miscible in water. Clean up in accordance with all applicable regulations.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Contact local authorities in case of spillage to drain/aquatic environment. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS). Do not allow material to freeze. If frozen, product may separate. Thaw completely at room temperature and stir thoroughly prior to use.

8. Exposure controls/personal protection

Occupational exposure limits

U.S. - OSHA

	Туре	Value	
SEVERELY-HYDROTREAT ED NAPHTHENIC PETROLEUM DISTILLATES (CAS 64742-52-5)	PEL	5 mg/m3	
U.S NIOSH			
	Туре	Value	
SEVERELY-HYDROTREAT ED NAPHTHENIC PETROLEUM DISTILLATES (CAS 64742-52-5)	STEL	10 mg/m3	
	TWA	5 mg/m3	
ACGIH			
	Туре	Value	
SEVERELY-HYDROTREAT ED NAPHTHENIC PETROLEUM DISTILLATES (CAS 64742-52-5)	TWA	5 mg/m3	

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Do not get in eyes. Eye wash fountain is

recommended.

Skin protection

Hand protection Nitrile gloves are recommended.

Other Wear appropriate chemical resistant clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Material name: POWER CUT SDS US

General hygiene considerations

When using, do not eat, drink or smoke. Do not get in eyes, on skin, on clothing. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance CLEAR
Physical state Liquid.
Form Liquid.

Form
Color
Not available.

Odor
CHEMICAL
Odor threshold
Not available.
Not available.
Not Applicable
Melting point/freezing point

A 32 °F (< 0 °C)
Initial boiling point and boiling

> 212 °F (> 100 °C)

range

Flash point 311 °F (155 °C) Cleveland Open Cup

Evaporation rate Like water when diluted

Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits

Flammability limit - lower (%)

Flammability limit - upper

(%)

Not available.

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Solubility(ies) 100 % Water Miscible

Partition coefficient

(n-octanol/water)

Relative density

Not available.

Not available.

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Explosive properties

Oxidizing properties

Ph in aqueous solution

Specific gravity

VOC ASTM D2369

Not explosive.

10.940

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible

materials.

Incompatible materials Acids. Oxidizing agents.

Hazardous decomposition

products

Smoke, fumes, hydrogen chloride, and oxides of carbon

Material name: POWER CUT

SDS US

11. Toxicological information

Information on likely routes of exposure

Inhalation Not classified.

Skin contact May cause an allergic skin reaction.

Eye contact Causes eye irritation.

Ingestion Not classified.

Symptoms related to the physical, chemical and

Direct contact with eyes may cause temporary irritation. Symptoms may include stinging, tearing,

redness, swelling, and blurred vision. May cause an allergic skin reaction.

toxicological characteristics

Information on toxicological effects

Acute toxicity

Components Species Test Results

ALKANES C14-16, CHLORO (CAS 1372804-76-6)

Acute Dermal

Liquid

LD50 Rabbit > 2000 mg/kg

Oral

Liquid

LD50 Rat > 5000 mg/kg

PETROLEUM SULFONIC ACID, SODIUM SALT (CAS 68608-26-4)

Acute

Dermal

Liquid

LD50 Rabbit > 2000 mg/kg ATE

SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES (CAS 64742-52-5)

Acute

Dermal

Liquid

LD50 Rabbit > 5000 mg/kg

Inhalation

Mist LC50

Rat 5.7 mg/l, 4 hours

Oral

Liquid

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation Not classified.

Serious eye damage/eye

irritation

Causes eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Material name: POWER CUT SDS US

^{*} Estimates for product may be based on additional component data not shown.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Not classified.

Further information The classification for health and environmental hazards is derived by a combination of calculation

methods and test data, if available.

12. Ecological information

EcotoxicityContains a substance which causes risk of hazardous effects to the environment.

Components Species Test Results

ALKANES C14-16, CHLORO (CAS 1372804-76-6)

Aquatic Acute

Fish LC50 Bluegill (Lepomis macrochirus) > 0.1 mg/l, 96 hours

SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES (CAS 64742-52-5)

Aquatic Acute

Fish LC50 Fish > 100 mg/l, 96 hours

Persistence and degradability Bioaccumulative potential

Mobility in soil This product is miscible in water.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN number UN3082

UN proper shipping name Environmentally hazardous substances, liquid, n.o.s. (ALKANES C14-16, CHLORO), MARINE

POLLUTANT

Transport hazard class(es)

Class 9
Subsidiary risk Label(s) 9
Packing group III

Environmental hazards

Marine pollutant Yes

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions 8, 146, 335, IB3, T4, TP1, TP29

Packaging exceptions 155
Packaging non bulk 203

Material name: POWER CUT SDS US

^{*} Estimates for product may be based on additional component data not shown.

Packaging bulk 241

Supplemental Information: 49CFR 171.4 excludes "non-bulk" packages (119 gallons or less) from Marine Pollutant Requirements unless all or part of the shipment is by vessel.

IATA

UN number UN3082

Environmentally hazardous substance, liquid, n.o.s. (ALKANES C14-16, CHLORO) **UN** proper shipping name

Transport hazard class(es)

9 Class Subsidiary risk Ш Packing group **Environmental hazards** Yes **ERG Code** 9L

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only

Allowed with restrictions.

IMDG

UN number UN3082

UN proper shipping name

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ALKANES C14-16,

CHLORO), MARINE POLLUTANT

Transport hazard class(es)

9 Class Subsidiary risk Packing group Ш

Environmental hazards

Marine pollutant Yes F-A, S-F

EmS


Transport in bulk according to

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Not established. Annex II of MARPOL 73/78 and

the IBC Code

DOT; IATA; IMDG



Marine pollutant



General information IMDG Regulated Marine Pollutant. DOT Regulated Marine Pollutant.

15. Regulatory information

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication US federal regulations

Standard, 29 CFR 1910.1200. It may be reportable under the provisions of SARA Sections 311

7/9

and 312 if specific threshold criteria are met or exceeded.

Material name: POWER CUT SDS US

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

TSCA Chemical Action Plans, Chemicals of Concern

ALKANES C14-16, CHLORO (CAS 1372804-76-6)

Short-Chain Chlorinated Paraffins (SCCPs) and Other Chlorinated

Paraffins Action Plan

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Not regulated.

Not regulated.

Food and Drug

Administration (FDA)

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a)

ALKANES C14-16, CHLORO (CAS 1372804-76-6)

SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES (CAS 64742-52-5)

California South Coast Air Quality Management District (SCAQMD) Rule 1144 (VOC Emissions) This product is subject to SCAQMD Rule 1144; it is compliant and may be sold and used in the SCAQMD. The VOC content of the product is 105 g/L, measured by ASTM Method E-1868-10. This product has a specified use dilution VOC limit of 75 g/L, the maximum dilution concentration

44 (VOC Emissions) is 71 % to maintain compliance.

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory or exempt (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No

Material name: POWER CUT SDS US

Country(s) or region Inventory name On inventory or exempt (yes/no)*

Philippines Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

 Issue date
 03-10-2015

 Revision date
 05-24-2018

Version # 03

Further information Not available.

NFPA ratings Health: 1
Flammability: 1
Instability: 0

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision informationThis document has undergone significant changes and should be reviewed in its entirety.

Material name: POWER CUT SDS US

No